

ProClean of Arizona, Inc.
P.O. Box 18250
Phoenix, AZ 85005
1-800-454-5544

MSDS
Material Safety Data Sheet
Complies with 29 CFR 1910.1200

Economy
Heavy Duty Lime Remover

Section I. Product Identification and Company Information

Product (Trade) Name: Heavy Duty Lime Remover
Manufacturer's Name: ProClean of Arizona, Inc.
Address: P.O. Box 18250 Phoenix, AZ 85005
Emergency Phone No.: 1-800-255-3924 **DOT Hazard Class:** Corrosive solution, acidic, inorganic,
Chemical Family: N/A Mixture n.o.s. (Phosphoric acid, Hydrochloric acid),
Formula: Trade Secret 8, UN 3264, II

Section II. Hazard Ingredients

Ingredient:	(CAS#)	% by Wt.	OSHA/PEL	ACGH TLV-TWA
Phosphoric acid	7664-38-2	25 - 35	5 ppm	1 mg/m ³
Hydrochloric acid	7647-01-0	10 - 23	1 mg/m ³	5 ppm
Ethane-1,2- dioic acid	144-62-7	3 - 8	1 mg/m ³	1 mg/m ³

Section III. Physical Data

pH-: <1.00 **Boiling Point:** N/D.
Physical State: Liquid **Freezing Point:** N/D.
Specific Gravity (H₂O=1): 1.17 **Vapor Pressure (mm hg):** N/D
Odor and Appearance: Acrid, clear light green **Solubility in Water:** Miscible
Percent Volatile by wt. (VOC): 0% **Evaporation Rate (H₂O=1):** 1

Section IV. Fire and Explosion Hazard

Flammability: Non Flammable **UFL (% by Volume):** N/A
Flash Point (Tag. Close Cup): N/A **LFL (% by Volume):** N/A
Special Fire Fighting Procedure: None **Explosion Data:** N/A
Unusual Fire and Explosion Hazards: None
Extinguish Media: Water, Carbon Dioxide, Dry Powder Extinguisher

Section V. Health Hazard

Primary Route of Exposure: Skin
Threshold Limit Value: N/D
Effects of Overexposure: Acute
By Inhalation: Causes severe burns to the respiratory tract.
By Eye Contact: May cause serious burns to the eyes resulting in visual impairment or blindness, depending of contact time.
By Indigestion: Corrosive poison. Indigestion may be fatal. Severe corrosion of the mouth, throat and digestive system, causing vomiting, abdominal pain, convulsion, and collapse.
By Skin Contact: May cause skin burns.
Emergency and First Aid Procedures: For Eye Contact: Flush with water for at least 15 minutes. Get medical attention immediately.

For Ingestion: Do not induce vomiting, contact a physician immediately.
For Skin Contact: Rinse area of contact with plenty of water.
For Inhalation: Remove to fresh air. If breathing has stopped, give artificial respiration

Section VI. Reactivity Data

Stability: Stable
Incompatibility (Material to Avoid): Alkalies, oxidizing agents, silver compounds, amines, alcohols, glycols, phenols, ketones, organic peroxides, amides, organophosphates.
Hazardous Combustion Products: Oxides of carbon and phosphorous, and other unidentified organic compounds
Hazardous Polymerization: Will not occur

Section VII. Spill and Disposal Procedures

Steps to be taken in the event of a spill or discharge: Contain for disposal and recovery
Clean area of any residual matter.
Waste Disposal Method: Dispose in accordance with all local, state, and federal regulations.

Section VIII. Protective Equipment

For Handling Product as Supplied:
Respiratory Protection: Not required
Ventilation: Normal ventilation is satisfactory
Protective Gloves: Wear rubber gloves
Eye Protection: Wear safety glasses
Other Protective Equipment (in case of a spill): Wear face shield and impermeable apron.
For Handling Product After Dilution for Use:
Respiratory Protection: Not required
Ventilation: Normal ventilation is satisfactory
Protective Gloves: Wear rubber gloves
Eye Protection: Wear Safety glasses.
Other Protective Equipment: Wear face shield and impermeable apron


Section IX. Storage and Handling Precautions

Store product in a cool area away from direct sunlight. Do not mix with any other product. Avoid using this product with water temperatures above 212 degrees F.

Section X. Transportation and Additional Information

This product liberates explosive hydrogen gas when reacting with chlorides and stainless steel. Will react violently with sodium tetrahydroborate.

Hazard Rating Scale: 0=Minimal 3=Serious
1=Slight 4=Severe
2=Moderate



Product: Heavy Duty Lime Remover

N/A = Not Applicable

Page 1 Revision Date: November 14, 2003

N/D = Not Determined

Prepared by: Werner Buchmann

N/E = Not Established

ProClean of Arizona, Inc.
P.O. Box 18250
Phoenix, AZ 85005
1-800-454-5544

ISP

Informacion de Seguridad para los Productos
Comple con los reglamentos del 29 CFR

Economy
Heavy Duty Lime Remover

Seccion I. Identificacion del Producto

Identificacion General o Generica: Heavy Duty Lime Remover

Nombre del Fabricante: ProClean of Arizona, Inc.

Direccion: P.O. Box 18250 Phoenix, AZ 85005

Telefono en Causa de Emergencia: 1-800-255-3924

Nombre Quimico: N/A Mistura DOT Clasificacion de Riesgo: Corrosive liquid, acid, inorganic,

Formula: Secreto industrial n.o.s. (Hydrochloric acid, Phosphoric acid), 8, UN 3264, III

Seccion II. Componentes

Ingrediente:	(CAS#)	% por peso	OSHA/PEL	ACGH TLV-TWA
Phosphoric Acid acid	7664-38-2	25 - 35	5 ppm	1 mg/m ³
Hydrochloric acid	7647-01-0	10 - 23	1 mg/m ³	5 ppm
Ethane,1,2- dioic acid	144-62-7	3 - 8	1 mg/m ³	1 mg/m ³

Seccion III. Informacion Fisica

pH-:	<1.00	Punto de Ebullicion:	N/D
Estado Fisico:	Liquido	Punto de Congelacion:	N/D
Gravidad Especifica (H ₂ O):	1.17	Presion de Vapor (mm hg):	N/D
Aparencia y Odor:	Acido, verde, translucido	Desolvente in Agua:	Completo
Porcento Volatil por Peso (VOC):	0%	Constante de Evaporacion (H ₂ O=1):	1

Seccion IV. Informacion de Fuego Y Explosion

Flamabilidad: No es Flamable	UFL (% por volume):	N/A
Punto de Ignicion (Tag. Close Cup): N/A	LFL (% por volume):	N/A
Caso Especial en Caso de Incendio: Nenguno	Informacion de explosion:	N/A
Incendios Especiales Y Riesgos de Explosion: N/A		
Material de Apagamiento de Fuegos: Agua, Dioxido de carbono, Dry Powder Extinguisher		

Seccion V. Informacion de Riesgo para la Salud

Ruta de Acceso Primario: El contacto es usualmente causado por salpicaduras

Threshold Limit Value: N/D

Efectos Criticos por Exposicion Excesiva: Agudo

Por Respiracion: Causa quemaduras severas al tracto respiratorio.

Por Contacto con los Ojos: Puede causar quemaduras severas a los ojos resultand en perda de la vision o ceguera, dependiendo del tiempo de contacto.

Por Digestion: Veneno corrosivo. Ingerir el producto puede ser fatal. Corrosior severa de la boca, garganta, y tracto digestivo, causando vomito, convulsion, y desplome.

Por Contacto a la Piel: Puede causar irritacion.

Procedimiento de Emergencia: Por Contacto con los ojos: Enjuague con agua cuando menos por 15 minutos. Consulte a su medico inmediatamente.

Product: Reavy Duty Lime Remover

N/A = No es Aplicable

Page 2 Revision Date: November 14, 2003

N/D = No es Determinado

Prepared by: Werner Buchmann

N/E = No es Establecido

Por Digestion: No se produzca el vomito, consulte a su medico inmediatamente.

Por Contacto con la Piel: Enjuague con agua cuando menos por 15 minutos.

Por Resporacion: Remova para aire fresco. Si no respira, produzca respiracion artificia

Seccion VI. Informacion de Reactividad

Estabilidad: Estable

Incompatibilidad con otros Materiales: Bases, quimicos oxidantes, compuestos de plata, amines, alcohols, glycols, phenols, ketones, peroxides organicos, amines, organophosphates.

Productos Peligrosos de Combustion : Dioxido de carbono, monoxido de carbonc

Y otros productos no indentificados.

Polimerizacion Peligrosa: No si ocurra

Seccion VII. Procedimiento en Caso de Goteo o Derrame

Procedimiento en Caso de Derrame o Goteo: Contena lo material y limpie qualque

residuo del producto.

Procedimiento de Desaecho: De acuerdo a las reguaciones locales, estaduales, y federales

Seccion VIII. Informacion de Equipo de Proteccion

Manejo del Producto Concentrado:

Proteccion Respiratoria:	No es requerida
Ventilacion:	Ventilacion normal es suficiente
Quantes de Proteccion:	Se require
Proteccion para los Ojos:	Se require

Equipo de Proteccion Extra (en caso de derramarse): Delantal para quimicos, proteccion para la cara.

Manejo del Producto Despues de diluir:


Proteccion Respiratoria:	No es requerida
Ventilacion:	Ventilacion normal es suficiente
Quantes de Proteccion:	No son requeridas
Proteccion para los Ojos:	No es requerida
Equipo de Proteccion Extra:	Delantal para chimicos, proteccion para la car:

Seccion IX. Precauciones de Almacenamiento Y Manejo

Mantenga el producto protegido del sol. No mezcle este producto con nenguno otro producto quimico. Evite usar este producto en temperaturas de agua mas alta que 212 F.

Seccion X. Ttransportacion Y Informaciones Adicionales

Este producto produce explosivo gas de hydrogenio por quando reacciona con acero inoxidable y cloratos. Este producto reacciona violentamente con tetrahydroborato de sodio.



Escala de Peligro:	0= Minimo	3=Serio
	1=Poco	4=Severo
	2=Moderado	