

MSDS

Brady Industries, HQ

Material Safety Data Sheet 4003
Conforms to ANSI Z-400.1-1993

Las Vegas , NV 89118
(800) 293-4698

1 Chemical Product and Company Identification

Product:Hard Surface Finish & Sealer

Classification: Floor Care

B30

2 Composition/Information on Hazardous Ingredients

| Material | CAS# | % | OSHA(PEL) | TLV(ppm) | Other |
|--------------------------------|----------|----|-----------|----------|-------|
| Diethylene Glycol Ethyl Ether* | 111-90-0 | <5 | 50 ppm | 50 ppm | N/A |
| Ethylene Glycol* | 107-21-1 | <3 | 50 ppm | 50 ppm | N/A |
| Tributoxyethyl Phosphate | 78-51-3 | <3 | N/E | N/E | N/E |

3 Hazards Identification

Emergency Overview: Irritant. May cause skin and eye irritation. Avoid contact with skin and eyes.

CAUTION

Contact with Eyes: Slightly irritating.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Product will be neutralized and coagulated by stomach acids. May irritate throat, stomach and esophagus.

Inhalation Symptoms: Excessive exposure to mists/vapors may irritate respiratory tract and result in headache and nausea.

Chronic Effects: No data.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult, give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute remaining residue. Seek medical attention.

3/6/2006 0001 4003

Hard Surface Finish & Sealer Page 1 of 3

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F

Flammable Limits: LEL No Data

UEL No Data

Auto Ignition Temperature:No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

None

Respiratory Protection:

None

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

