

ProClean of Arizona, Inc.
P.O. Box 18250
Phoenix, AZ 85005
1-800-454-5544

MSDS
Material Safety Data Sheet
Complies with 29 CFR 1910.1200

ProClean
Pro Boost

Section I. Product Identification and Company Information

Product (Trade) Name: Pro Boost
Manufacturer's Name: ProClean of Arizona, Inc.
Address: P.O. Box 18250 Phoenix, AZ 85005
Emergency Phone No.: 1-800-255-3924
Chemical Family: N/A Mixture **DOT Hazard Class:** Corrosive liquid, basic,
Formula: Trade Secret inorganic, N.O.S. (Potassium hydroxide), 8, UN 3266, II

Section II. Hazard Ingredients

Ingredient:	(CAS#)	% by Wt.	OSHA/PEL	ACGH TLV-TWA
Potassium Hydroxide	1310-58-3	25- 35	2 mg/m ³	2 mg/m ³
Silicic acid disodium salt	6834-92-0	2 - 5	2 mg/m ³	2 mg/m ³

Section III. Physical Data

pH-: 14.00 **Boiling Point:** N/D
Physical State: Liquid **Freezing Point:** N/D
Specific Gravity (H₂O=1): 1.29 **Vapor Pressure (mm hg):** N/D
Odor and Appearance: Odorless, opaque off white **Solubility in Water:** Miscible
Percent Volatile by wt. (VOC): 0% **Evaporation Rate (H₂O=1):** 1

Section IV. Fire and Explosion Hazard

Flammability: Non Flammable **UFL (% by Volume):** N/A
Flash Point (Tag. Close Cup): N/A **LFL (% by Volume):** N/A
Special Fire Fighting Procedure: None **Explosion Data:** N/A
Unusual Fire and Explosion Hazards: None
Extinguish Media: Water, Carbon Dioxide, Dry Powder Extinguisher

Section V. Health Hazard

Primary Route of Exposure: Skin
Threshold Limit Value: N/D
Effects of Overexposure: Acute. Corrosive to all body tissues by all routes of exposure.
By Inhalation: Breathing mist or spray may cause damage to the upper respiratory tract.
By Eye Contact: Causes severe burns that result in damage to the eyes, and possibly blindness depending on concentration and how soon after exposure the eyes are washed.
By Indigestion: Causes severe burns to mucos membranes of the mouth, throat, esophagus, and stomach.
By Skin Contact: Contact produces severe burns and destroy tissue. Irritation may be delayed
Emergency and First Aid Procedures: For Eye Contact: Flush with water for at least 15 minutes. **Get medical attention immediately.**

Product: Pro Boost

Page 1 **Revision Date:** October 02, 2008

Prepared by: Werner Buchmann

N/A = Not Applicable

N/D = Not Determined

N/E = Not Established

For Ingestion: Do not induce vomiting. Contact a physician immediately.

For Skin Contact: Rinse area of contact immediately with water for 15 minutes. Consult a physician if irritation persists.

Section VI. Reactivity Data

Stability: Stable
Incompatibility (Material to Avoid): Acids, aluminum, tin, zinc, alloys containing these metals, and strong oxidizing agents.
Hazardous Combustion Products: Carbon dioxide, carbon monoxide, and other unidentified organic compounds
Hazardous Polymerization: Will not occur

Section VII. Spill and Disposal Procedures

Steps to be taken in the event of a spill or discharge: Contain for disposal and recovery.

Neutralize it with a 20% citric acid solution. Clean area of any residual matter.

Waste Disposal Method: Dispose in accordance with all local, state, and federal regulations.

Section VIII. Protective Equipment

For Handling Product as Supplied:

Respiratory Protection: Not required
Ventilation: Normal ventilation is satisfactory
Protective Gloves: Wear rubber gloves
Eye Protection: Wear safety glasses
Other Protective Equipment: Wear protective apron and face shield.

For handling Product After Dilution for Use:

Respiratory Protection: Not required
Ventilation: Normal ventilation is satisfactory
Protective Gloves: Not required
Eye Protection: Not required
Other Protective Equipment: Not required

Section IX. Storage and Handling Precautions


Store product in a cool area away from direct sunlight. Do not mix with any other product.

Section X. Transportation and Additional Information

If necessary to mix with water or to neutralize it with citric acid, mix slowly and with agitation

to avoid a violent exothermic reaction. Do not mix with strong acids without dilution and agitation. Flammable hydrogen gas may be produced on prolonged contact with Aluminum, tin, zinc, and led.

Hazard Rating Scale: 0=Minimal 3=Serious
1=Slight 4=Severe
2=Moderate



ProClean of Arizona, Inc.
P.O. Box 18250
Phoenix, AZ 85005
1-800-454-5544

ISP

Informacion de Seguridad para los Productos

Comple con los reglamentos del 29 CFR 1910-1200

ProClean Pro Boost

Seccion I. Identificacion del Producto

Identificacion General o Generica: Pro Boost
Nombre del Fabricante: ProClean of Arizona, Inc.
Direccion: P.O. Box 18250 Phoenix, AZ 85005
Telefono en Causa de Emergencia: 1-800-454-5544
Nombre Quimico: N/A Mistura **DOT Clasificacion de Riesgo:** Corrosive liquid,
Formula: Secreto Industrial basic, inorganic, N.O.S. (Potassium hydroxide), 8, UN 3266, II

Seccion II. Componentes

Ingrediente:	(CAS#)	% por peso	OSHA/PEL	ACGH TLV-TWA
Potassium Hydroxide	1310-58-3	25 - 35	2 mg/m ³	2 mg/m ³
Silicic acid disodium salt	6834-92-0	2 - 5	2 mg/m ³	2 mg/m ³

Seccion III. Informacion Fisica

pH-:	14.00	Punto de Ebullicion:	N/D
Estado Fisico:	Liquido	Punto de Congelacion:	N/D
Gravidad Especifica (H₂O):	1.29	Presion de Vapor (mm hg):	N/D
Aparencia y Olor:	Sin olor, opaco blanco	Desolvente in Agua:	Completo
Porcento Volatil por Peso (VOC):	0%	Constante de Evaporacion (H₂O=1):	1

Seccion IV. Informacion de Fuego Y Explosion

Flamabilidad: No es Flamable	UFL (% por volume): N/A
Punto de Ignicion (Tag. Close Cup): N/A	LFL (% por volume): N/A
Caso Especial in Caso de Incendio: Ninguno	Informacion de explosion: N/A
Incendios Especiales Y Riesgos de Explosion: N/A	
Material de Apagamiento de Fuegos: Agua, Dioxido de carbono, Dry Powder Extinguisher	

Seccion V. Informacion de Riesgo para la Salud

Ruta de Acceso Primario: El contacto es usualmente causado por salpicaduras
Threshold Limit Value: N/D
Efectos Criticos por Exposicion Excesiva: Agudo. Corrosivo por todas las rutas de acceso.

Por Respiracion: Respirar a niebla o spray puede causar danos al sistema respiratorio.

Por Contacto con los Ojos: Causa quemaduras quimicas severas a los ojos que pueden tener danos permanentes y ceguera, dependente a concentracion e quanto tiempo antes de enjuagar los ojos.

Por Digestion: Causa quemaduras quimicas severa a las membranas mucosas de la boca, garganta, esophago, y estomago.

Por Contacto a la Piel: Causa quemaduras quimica severas. Irritacion puede ser retardada.

Procedimiento de Emergencia: Por Contacto con los ojos: Enjuague con agua cuando menos por 15 minutos. **Consulte a su medico inmediatamente.**

Product: Pro Boost

Page 2 Revision Date: October 02, 2008

Prepared by: Werner Buchmann

N/A = No es Aplicable

N/D = No es Determinado

N/E = No es Establecido

Por Digestion: No se produzca el vomito, consulte a su medico inmediatamente.

Por Contacto con la Piel: Enjuague con agua cuando menos por 15 minutos. Consulte a su medico si irritacion a la piel continuar.

Seccion VI. Informacion de Reactividad

Estabilidad: Estable
Incompatibilidad con otros Materiales: Acidos, aluminio, estano, zinc, ligas con estos metales, y quimicos oxidantes fuertes.

Productos Peligrosos de Combustion : Dioxido de carbono, monoxido de carbono,

Y otros productos no indentificados.

Polimerizacion Peligrosa: No si ocurra

Seccion VII. Procedimiento en Case de Goteo o Derrame

Procedimiento en Caso de Derrame o Goteo: Contena lo material y neutralize-lo con

una solucion de 20% de acido citrico. Limpie qualquer residuo del producto.

Procedimiento de Desaecho: De acuerdo a las regulaciones locales, estatales, y federales.

Seccion VIII. Informacion de Equipo de Proteccion

Manejo del Producto Concentrado:

Proteccion Respiratoria:	No es requerida
Ventilacion:	Ventilacion normal es suficiente
Quantes de Proteccion:	Se require
Proteccion para los Ojos:	Se require
Equipo de Proteccion Extra:	Delantal para quimicos y proteccion para la cara.

Manejo del Producto Despues de diluir:

Proteccion Respiratoria:	No es requerida
Ventilacion:	Ventilacion normal es suficiente
Quantes de Proteccion:	No son requeridas
Proteccion para los Ojos:	No es requerida
Equipo de Proteccion Extra:	No es requerido

Seccion IX. Precauciones de Almacenamiento Y Manejo

Mantenga el producto protegido del sol. No mezcle este producto con nenguno otro producto quimico. Flamable gas de hydrogenio puede se formar por quando en contacto con metales.

Seccion X. Transportacion Y Informaciones Adicionales

Se es necesario mesclar este producto, mescle con despacio y agitacion para evitar una violenta reaccion exotermica. Nunca mescle este producto con acidos fuertes sin antes diluir el acido y con mucha agitacion.

Escala de Peligro: 0=Minimo 3=Serio
1=Poco 4=Severo
2=Moderado

